## Combustible Gas Detector Catalytic Bead Model C920L Series







C920L - LED Display
With Light and Sound Alarm

EASE AT INSTALLATION AND MAINTENANCE
FLEXIBLE FOR INDUSTRY STANDARD PROTOCOLS
THE RIGHT CHOICE FOR YOUR GAS DETECTION APPLICATION



## Combustible Gas Detector — Catalytic Bead C920L Series

## MAKING INSTALLATION AND EVERYDAY OPERATION EASY

The C920L Series is full-featured 4-20mA, loop powered transmitters especially designed for comprehensive ranges of combustible gas detection. The interface enables the detector to be calibrated and operated with the explosion-proof enclosure in place. Universal electronics and user-friendly features make the C920L ease of maintenance, cost effective, and suitable for various industries.

SPECIFICATIONS	
Operating Voltage	10-30 VDC (24 VDC nominal)
Power Consumption	< 2.0 Watts
Enclosure Material	Aluminum
Enclusure Ingress Protection	IP 67
Terminal Junction Box Connection	3/4" NPT
Communication	4–20 mA
Response Time	T90:<30S
Alarms	Programmable alarms
Relays	3A 250VAC, 3A 30VDC
Display	4-digit LED 7 segments
	Display indicates status Normal, Fault, Low Alarm, and High Alarm
	Display provides simple, intuitive calibration instructions and guides user through the calibration
Languages	English
ENVIRONMENTAL	
Operating Temperature	-40° to 70° C
Humidity	(10-95)% RH (non-condensing)
Storage Temperature	-55° to 70° C
APPROVALS	
Area Classification	ATEX (Ex d II CT6Gb)
INSTALLATION	
Weight	1.38 kg
Wiring	3-wires
SENSOR SPECIFICATION	
Sensor Type	Catalytic Bead

## The C920L is available in full-range of combustible gases:

Distributed By:



Canadian Safety Co., Ltd. 11781 Cascade Drive Delta B. C. Canada V4E 3C3

Tel: (+1) 613 555 0122 info@cs-canadiansafety.com